

CVS QUICK REFERENCE CARD

Overview

CVS is a version control system aimed at keeping an history and managing multiple people working at the same time on a same source hierarchy. CVS keeps a single copy of the master sources, called the *repository*. Each person works on one's own copy of the repository, called the *sandbox*. CVS allows one to control the changes between its sandbox and the global repository.

Synopsis

`cvs [cvsopt] cmd [cmdopt] files...`

`cvsopt`... options controlling the overall CVS program
`cmd`... particular action to perform on the repository
`cmdopt`... options controlling the specific command
`files`... files to act on, or specific arguments to `cmd`
If you do not specify any files, CVS will normally recurse into subdirectories and apply the command to each CVS files encountered. **Warning:** the same option can mean different things depending on whether it is in the `cvsopt` or `cmdopt` group.

Overall CVS options

This list describes all possible `cvsopt` available.

- b *bindir*... use *bindir* as location of RCS files
 same as the RCSBIN environment variable
- d *cvsdir*... use *cvsdir* as location of repository
 same as the CVSROOT environment variable
- e *editor*... use *editor* to enter log information
 same as the CVSEEDITOR or EDITOR variable
- f... do not read the `/.cvsrc` startup file
- H... display a summary of all commands available
- H *cmd*... display usage information about *cmd*
- l... do not log the command in history
- q... be quiet, suppress informational messages
- Q... be *really* quiet, output only serious problems
- n... do not change any files, only simulate
- r... make new working file read-only
 same as if CVSREAD variable is set
- t.. trace program execution, useful with -n to explore
- v... display version and copyright information
- w... make new working file read-write (default)
- x... encrypt communication between client & server
- z *n*... use *n* as compression level for transferring files

CVS command summary

This list summarizes all possible `cmd` available. Only `cmd` ticked with ▷ are detailed here.

- ▷ **add**... add new files or directories
- admin**... control/administrate the repository
- ▷ **checkout**... get a new sandbox from the repository
- ▷ **commit**... apply changes, additions, deletions
- ▷ **diff**... show differences between sandbox & repository
- export**... prepare copies for off-site shipment
- ▷ **history**... show report on commands executed
- ▷ **import**... incorporate a set of off-site updates
- init**... initialize a new repository
- ▷ **log**... show stored log information
- rdiff**... prepare a collection of diffs as patch file
- release**... cancel a **checkout**, abandoning changes
- ▷ **remove**... remove files from the source tree
- rtag**... specify a symbolic tag for a revision
- ▷ **status**... show current status of files
- ▷ **tag**... specify a symbolic tag from a sandbox
- ▷ **update**... get the changes from the repository

Common command options

This list describes all possible `cmdopt` available, common for all `cmd`, except **history**. Not all commands support all options, only when it makes sense. The `o` symbol specifies a sticky option (CVS remembers the option on subsequent commands).

- o -D*date*... the most recent revision no later than *date*
 1 month ago, 6/29/97 08:20:00 PST,
 yesterday, last Friday, 18:30 GMT...
- f... use file even if it does not match tag or date
- o -kb... set the file as binary (do not expand keywords)
- o -kv... retain keyword information
- l... disable recursion in sub-directories
- n... do not run program associated with `cmd`
- P... remove empty directories after **checkout**/**update**
- p... pipe files from the repository to standard output
- o -r *tag*... use the revision *tag* instead of head
 use HEAD for the latest version available
 or BASE for the file you last checked out

Checkout

`cvs co [-ANPRcflnps] [-rrev|-Ddate] [-ddir] [-jrev1
[-jrev2]] [-kopt] module...`

Obtain a new sandbox by getting files from *module* into the directory CVS creates. `cvs co` in an already checked out module is identical to `cvs upd -d`.

- A... reset any sticky (o) tags, flags, dates
- j*v*... merge changes from the revision *v*
- j*v1* -j*v2*... merge changes from *v1* & *v2*
- N... avoid shortening modules paths
- c... only list all module files to standard output
- ddir... use *dir* for new directory instead of module
- s... display status information for each module

Commit

`cvs ci [-nRlf] [-m'msg'|-Ffile] [-rrev] files...`

Incorporate changes made locally in the sandbox back into the repository.

- R... force recursion when scanning for files
- l... disable recursion in sub-directories
- f... force commit even if no change has been made
- F*file*... use content of *file* as log message
- m*msg*... specify *msg* as log message
- rrev... commit to specific revision *rev*

Update

`cvs upd [-APdflRp] [-rtag|-D date] [-jrev] [-Iign]
[-kopt] [-Wspec] files...`

Update the sandbox with external changes made to the repository.

- A... reset any sticky (o) tags, flags, dates
 - jrev... merge changes from the revision *rev*
 - d... create any new directories from the repository
 - If... ignore file whose names match *f*
 - I!... avoid ignoring any file at all
 - C... overwrite locally modified files with clean copies
- The `cvs upd` prints a status flag for each file:
- U... brought up to date with the repository
 - A... added locally but not yet committed
 - R... removed locally but not yet committed
 - M... modified locally or merged with the repository
 - C... conflicting merge that needs manual resolution
 a backup copy is made under `.#file.version`
 - ?... ignored local file which does not exist in repository

Remove

`cvs remove [-f|lR] files...`

Remove files or directories from repository.

`-f`delete the file before removing it

Add

`cvs add [-kkflag] [-m' msg'] files...`

Add new files or directories to repository.

`-kkflag`use `kflag` for RCS

`-m' msg'`use `msg` as the creation log

Differences

`cvs diff [-lNR] [-rr1 [-rr2] | -Dd2 [-Dd1]] files...`

Show differences between sandbox and repository.

`-Dd1`diff working file against date `d1`

`-Dd1 -Dd2`diff date `d1` against date `d2`

`-rr1`diff working file against revision `r1`

`-rr1 -rr2`diff revision `r1` against revision `r2`

`-N`include added/removed files

Log

`cvs log [-lRhtNb] [-rr1[:r2]] [-dd1 [d2]] [-sstates]`

`[-wlogins] files...`

Show log information stored for some files.

`-R` print name of RCS file only

`-h`print header only

`-t`print header and description only

`-N`do not list tags

`-b` list default branch revisions only

`-rrevs` specify set of revisions to list

`-ddates` specify set of dates to list

`-sstates` specify set of states to list

`-wlogins` ...list only revisions checked in by users `logins`

Import

`cvs import [-d] [-bbranch] [-Ifile...] rep vendor release`

Incorporate a new hierarchy of sources under CVS.

`rep`directory path, eventually creates it

`vendor`tag used for the entire branch

`release` tag used for the imported files

`-d` ...use file's last modification time for check-in time

`-bbranch` ...specify a branch `branch` other than 1.1.1

`-Iname` ignore file `name` for import

History

`cvs hist [-Tcoelw] [-mmodule] [opts] files...`

Show a report on CVS commands that you or others have executed on a particular file or directory in the source repository. **Warning:** uses options in ways conflicting with common meaning.

`-T` report on all tags

`-c` report on each commit

`-o` report on checked-out modules

`-e` report on everything

`-a` report data for all users

`-l` report on last modification only

`-w` report on the current directory only

`-mmod` report on module `mod`

`-xtype` extract record `type`, a list of several letters:

O checked-out	A first added
W deleted during an update	T rtagged
U copied from repository	M modified
G merged with success	F released
C merged with conflict	R removed

`-bstr` up to module/file/path matching `str`

`-Ddate`report since `date`

`-prep` report for repository `rep`

`-uuser`report for user `user`

Status

`cvs status [-lRqQ] [-v] files...`

Display a brief report on the current status of `files`: latest version, version in working directory, whether the working version has been edited and, optionally, symbolic tags in the RCS file.

`-v` display also RCS file symbolic tags

Tags

`cvs tag [-lRqQ] [-Fbd] [[-rtag | -Ddate] [-f]] tag files...`

Specify a symbolic tag for files in the repository. By default tag the revision that were last synchronized with your working directory. Applied immediately to the repository.

`-r -D`used to rename an already-existing tag

`-f` used with `-r` & `-D`, force the tag

`-F` move the tag if it already exists

`-b`apply the tag as a new branch

`-d` delete the tag instead of adding it

Keywords

Embedded strings `$keyword:...$` in text files are updated by CVS whenever getting a new revision.

`$Author$` ...login name of the user who last checked in

`$Date$`UTC date & time of the last check in

`$Header$`RCS file, rev., date, author, state, locker

`Id`same as `$Header$` without path

`$Name$` tag name used to check out the file

`$Locker$` ... login name of the user who locked the file

`Log` log message preceded by a header (append)

`$RCSfile$`RCS file without a path

`$Revision$`current revision number

`$Source$` RCS file full pathname

`$State$`state assigned to the revision

Administrative files

Files that CVS keeps under `CVS/`. Do not delete them.

`Entries`list and status of working files

`Entries.Static` ... do not add more files on `cvs upd`

`Root` pathname used if `CVSROOT` is not defined

`Repository`pathname to the repository directory

`Tag`sticky date or tag per directory

`Checkin.prog`program to run on `cvs ci`

`Update.prog`program to run on `cvs upd`

Environment variables

Here is a list of environment variables that CVS uses.

`CVSROOT` pathname to the repository root

`CVSREAD` ... if set, `co` and `upd` will make files read-only

`CVSEditor`program to use for commit log message

`EDITOR` used if `CVSEditor` is not set

Ignoring special files

Contains a list of file patterns that CVS should ignore.

`CVSROOT/cvsignore` per-repository file

`~/cvsignore` per-user file in home directory

`$CVSIGNORE` environment variable

`-If` command-line option

`.cvsignore` ... per-directory in sandbox, not recursive

`!` ...clear current list, except per-directory `.cvsignore`

This card may be freely distributed under the terms of the GNU general public licence — Copyright © 2006 by Laurent Grégoire (laurent.gregoire@icam.fr) — v0.4 — The author assumes no responsibility for any errors on this card. The latest version can be found at <http://tnerual.eriogerg.free.fr/>